

TDL 88 IP65



PRODUCT CODE # 88WC930AP002

RECESSED LED DOWNLIGHT



LIGHT SPECIFICATION

- LED module: Philips COB G7 930
- Color temp: 3000K
- CRI: 93
- Lumen output: 780lm
- Power: 7.2W
- Beam angle: 48°
- Tilt: Fixed
- Trim color: NCS S 0500-N
- Dimensions (D x H): ø88 x 60 mm > installation depth
- Body material: Aluminium, steel housing > B0
 - (B15 with specific ceiling)
- IP class: IP65
- Dimming: DALI 1-100%
- Lumen maintenance:
 - Tc nom 85°C L70B20 – 50 000h
 - Tc 65°C L80B10 – 50 000h

ADDITIONAL SPECIFICATION

- Driver: Osram OTi DALI 15
- Driver power: 11W
- Output current: 206 mA
- Output voltage: 35 V
- Rset resistor: 24kΩ
- Power supply: 220-240V 0/50/60Hz
- Electrical interface: 0,2 m connection cable
- Connector: WAGO MIDI 770-1115
- Working temp. range: -20 °C ... - + 45°C
- Cutout: Ø62mm
- Weight: 530g (total)
- Fixing method: Fixing with screws



TVV Marine Lighting Oy,
Jousitie 2C, 20760 Piispanristi, Finland
mobile : +358 440501007 | info@tvvmarinelighting.com | www.tvvmarinelighting.com